

Ref. **9DWKT80**

Synthetic Boots

PVC

Boots



S5



MADE IN EUROPE



LG

### The +

- \*Excellent grip thanks to an oil-resistant sole.
- \*Highest SR class anti-slip power, for perfect grip on all terrains. \*Energy absorption in the heel area.
- \*Improved fit and support

### PURCHASE PACKAGING

Ref.	Size	Carton
9DWKT80036	36	6
9DWKT80037	37	6
9DWKT80038	38	6
9DWKT80039	39	6
9DWKT80040	40	6
9DWKT80041	41	6
9DWKT80042	42	6
9DWKT80043	43	6
9DWKT80044	44	6
9DWKT80045	45	6
9DWKT80046	46	6
9DWKT80047	47	5

*Some sizes may only be available in certain countries*

### DESCRIPTION

The Work-it boot is a waterproof safety boot made from recycled PVC and lined with polyester. Non-slip on ceramic floors, its PVC sole is also antistatic and resistant to hydrocarbons. This work boot is equipped with a protective shell as well as a steel midsole against shocks and penetration.

### SECTORS

Farming, silviculture and fishing

Light Industries

Regional/public authorities

Infrastructure, building industry

DIY

## TECHNICAL FEATURES

Color	Green
Color 2	Black
Weight	1096g
Upper	PVC
Toecap	Steel
Puncture resistant sole	Stainless steel
Outsole	PVC nitrile
Lining	Polyester

## INSTRUCTION FOR USE AND STORAGE

**Instructions for use**

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

**Storage instructions**

Place the boots, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

**Washing instructions**

Regularly clean the boots by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

## STANDARD(S)



EPI CAT. II

EN ISO 20345:2022

S5

Safety shoes

S5 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe 0,1M? A < 1000 M? + Fuel and oil resistant contact outsole + Energy absorbing heel E ? 20 Joules + Spiked outsole + Puncture resistant midsole

SR

Resistance to slippage (ceramic floor + oil)

LG

Grip System - Unhooked heel